

Теплова потужність згідно EN 442

Тип	300 mm				400 mm				500 mm			
	11	21	22	33	11	21	22	33	11	21	22	33
W/м.п при 75/65/20 °C	509 W	744 W	933 W	1.347 W	676 W	927 W	1.173 W	1.686 W	833 W	1.107 W	1.401 W	2.007 W
400	163 103	239 153	299 190	430 271	216 137	298 191	376 239	538 340	267 170	355 227	449 286	641 404
500	203 129	299 192	374 238	538 339	271 172	372 238	470 299	673 424	334 213	444 283	561 357	801 505
600	244 154	359 230	449 285	645 407	325 206	447 286	564 359	808 509	401 255	533 340	674 428	961 606
700	285 180	419 269	523 333	753 475	379 240	521 333	658 418	942 594	468 298	622 397	786 500	1.122 707
800	325 206	479 307	598 380	860 542	433 275	596 381	752 478	1.077 679	534 340	711 453	898 571	1.282 808
900	366 231	539 345	673 428	968 610	487 309	670 429	846 538	1.211 764	601 383	800 510	1.011 643	1.442 910
1000	407 257	599 384	748 475	1.075 678	541 343	745 476	940 598	1.346 849	668 425	889 567	1.123 714	1.602 1.011
1100	447 283	658 422	822 523	1.183 746	595 377	819 524	1.034 657	1.480 934	735 468	977 623	1.235 785	1.762 1.112
1200	488 308	718 460	897 570	1.290 814	649 412	894 572	1.128 717	1.615 1.019	801 510	1.066 680	1.347 857	1.923 1.213
1400	569 360	838 537	1.047 665	1.505 949	758 480	1.043 667	1.316 837	1.884 1.188	935 595	1.244 793	1.572 1.000	2.243 1.415
1600		958 614	1.196 760	1.720 1.085	866 549	1.192 762	1.504 956	2.153 1.358	1.069 680	1.422 907	1.797 1.142	2.564 1.617
1800		1.077 691	1.346 855	1.935 1.221	974 618	1.341 857	1.692 1.076	2.423 1.528	1.202 765	1.599 1.020	2.021 1.285	2.884 1.819
2000		1.197 767	1.495 950	2.150 1.356	1.082 686	1.490 953	1.880 1.195	2.692 1.698	1.336 850	1.777 1.133	2.246 1.428	3.204 2.021
2200		1.317 844	1.645 1.045	2.366 1.492		1.639 1.048	2.068 1.315	2.961 1.867	1.469 935	1.955 1.247	2.470 1.571	3.525 2.223
2400		1.437 921	1.794 1.140	2.581 1.627		1.788 1.143	2.256 1.434	3.230 2.037	1.603 1.020	2.132 1.360	2.695 1.714	3.845 2.425
2600			1.944 1.235	2.796 1.763			2.444 1.554				2.920 1.857	
2800			2.093 1.331	3.011 1.899			2.632 1.673				3.144 1.999	
3000			2.243 1.426	3.226 2.034			2.820 1.793				3.369 2.142	

Тип	600 mm				700 mm				900 mm			
	11	21	22	33	11	21	22	33	11	21	22	33
W/м.п при 75/65/20 °C	980 W	1.287 W	1.617 W	2.313 W	1.117 W	1.467 W	1.824 W	2.607 W	1.360 W	1.836 W	2.220 W	3.180 W
400	315 201	413 263	518 330	739 466	359 229	470 298	585 372	833 525	437 279	587 370	712 453	1.016 641
500	394 251	516 328	648 412	923 582	449 286	587 373	731 465	1.041 656	546 349	733 463	890 567	1.269 801
600	472 302	619 394	778 495	1.108 699	538 344	705 447	877 558	1.249 788	655 419	880 556	1.068 680	1.523 961
700	551 352	722 459	907 577	1.293 815	628 401	822 522	1.024 651	1.457 919	765 488	1.027 648	1.246 793	1.777 1.121
800	630 402	825 525	1.037 660	1.477 932	718 458	940 596	1.170 744	1.665 1.050	874 558	1.173 741	1.424 907	2.031 1.281
900	708 452	929 591	1.167 742	1.662 1.048	807 516	1.057 671	1.316 837	1.873 1.182	983 628	1.320 833	1.602 1.020	2.285 1.442
1000	787 503	1.032 656	1.296 824	1.847 1.165	897 573	1.175 745	1.462 930	2.081 1.313	1.092 698	1.467 926	1.780 1.133	2.539 1.602
1100	866 553	1.135 722	1.426 907	2.031 1.281	987 630	1.292 820	1.609 1.023	2.289 1.444	1.201 767	1.613 1.019	1.958 1.247	2.793 1.762
1200	944 603	1.238 788	1.555 989	2.216 1.398	1.077 687	1.410 895	1.755 1.116	2.498 1.575	1.311 837	1.760 1.111	2.136 1.360	3.047 1.922
1400	1.102 704	1.444 919	1.815 1.154	2.585 1.631	1.256 802	1.644 1.044	2.047 1.303	2.914 1.838	1.529 977	2.053 1.296	2.492 1.586	3.554 2.243
1600	1.259 804	1.651 1.050	2.074 1.319	2.954 1.864	1.435 917	1.879 1.193	2.340 1.489	3.330 2.101	1.748 1.116	2.346 1.482	2.848 1.813	4.062 2.563
1800	1.417 905	1.857 1.182	2.333 1.484	3.324 2.096	1.615 1.031	2.114 1.342	2.632 1.675	3.746 2.363	1.966 1.256	2.640 1.667	3.204 2.040	4.570 2.883
2000	1.574 1.005	2.063 1.313	2.592 1.649	3.693 2.329	1.794 1.146	2.349 1.491	2.925 1.861	4.163 2.626	2.185 1.395	2.933 1.852	3.560 2.266	5.078 3.204
2200	1.732 1.106	2.270 1.444	2.852 1.814	4.062 2.562								
2400	1.889 1.206	2.476 1.575	3.111 1.979	4.432 2.795								
2600			3.370 2.144									
2800			3.629 2.309									
3000			3.889 2.473									

EN442 (W) 70/55/20 °C

EN442 (W) 55/45/20 °C